

3200 High Performance D/S Tape	Ref: 3200	
-----------------------------------	-----------	---

1. Product Description / Application

Rev 2024

High performance double sided self-adhesive tape with a cloth carrier and a clear high tack synthetic rubber adhesive.

3200 is designed for carpet laying and floor covering. Also used in a vast number of construction applications.

2. Key Characteristics

- Extremely high initial tack adhesive and permanent bonding capabilities.
- Tear resistant
- Enhanced Plasticizers resistant

3. Product Specification

Liner: 80 gsm brown two side siliconized paper

Carrier: PET cloth

Adhesive: Clear synthetic rubber

4. Product Data

ELONGATION (AFERA 5004)	[%]	tipic 10
TENSILE STRENGTH (AFERA 5004)	[N/cm]	28
180° PEEL (AFERA 5001)	[N/25mm]	>17
STATIC SHEAR (AFERA 5012)	[h]	>10
ROLLING BALL TACK (PSTC 6)	[cm]	<4
THICKNESS (AFERA 5006)	[μ]	190
THICKNESS LINER (AFERA 5006)	[μ]	70
PERFORMING TEMPERATURE	min -10 °C	max +50 °C

Important Notice

All UKIT products are subjected to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning UKIT products is based upon research, which the Company believes to be reliable, but some information does not constitute a warranty. Because of the variety of possible uses for UKIT products and continuing development of new uses, the purchaser should carefully consider the fitness and performance of the product for each intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential damages. All specifications are subject to change without prior notice.